

Degafloor LM

Manufactured from technically advanced methyl methacrylate resin, Degafloor LM is the ideal product for creating crisp and clear lines and other stencil applied markings. Based on heavy duty BAST (German Road Institute) certificated road marking resins, the LM system offers outstanding durability.

Applied using manual techniques (screed box, trowel or roller), the system is designed to provide excellent performance, flexibility and resistance to extreme operating conditions.

Suitable for both asphalt and concrete substrates.

Features and benefits

■ Rapid installation, minimal disruption

Cures within just 30 minutes of installation

■ Outstanding durability

Up to 3 x the life expectancy of traditional products

■ Excellent reflectivity (when used with glass beads)

Safe and bright

■ Cold applied

None of health and safety issues associated with hot trades, no big vehicles, minimised environmental impact

■ UV resistant

Provides crack free performance and colour stability

■ Incredibly strong bond to concrete and asphalt substrates

■ Exceptional skid resistance

That can be tailored

■ Solvent free

■ Excellent chemical and road salt resistance

■ Superb thermal stability

No softening / degradation during summer months, flexible in winter months

Fields of application include:

- Car park bay marking
- Arrows, lettering and other stencil applied markings
- Carriageway line re-instatement
- Petrol stations
- Airports (non-runway)



Degafloor 

Degafloor LM

Substrate preparation

All substrates must be clean, dry and free from contamination. Concrete substrates must be capable of accepting a resin finish and this is best achieved by mechanical means (shotblasting, planing or diamond grinding).

Concrete substrates may require priming using Degafloor 112 primer applied at approx. 0.4kg/m² (always conduct a bond test to test suitability of substrate).

Asphalt substrates do not require separate priming.

Cure times

Degafloor LM cures fully within just 30 minutes of installation (both chemically and physically). The cure time remains unaffected at temperatures down to -10°C.

Chemical resistance

Excellent resistance to diesel, engine oils and road salts. Limited resistance to unleaded and super unleaded petrol.

Standard colours available

Traffic Yellow (RAL1023)
White

Available pack sizes

25kg



Health and Safety

All resins are manufactured to ISO 9001:2008, ISO 14001:2004 and BS OHSAS 18001:2007 standards and comply with all current EU hygiene of foodstuffs regulation.

All resins are non-toxic and certified to confirm physiological inoffensiveness.

Disclaimer

Degafloor Ltd endeavour to ensure that all information and advice given is accurate and correct. However, the company cannot take responsibility for the selection of products for specific applications. Therefore any prospective customers should satisfy themselves that the product is suitable for the environment in which it will be installed. Accordingly, Degafloor cannot take responsibility for the selection, by others, of a product unsuitable for the application. The information detailed in this leaflet is liable to change without prior notification.

Degafloor Ltd, Crusader House, High Street,
Maxey, Peterborough UK PE6 9HQ

T: +44 (0)1778 342 545 F: +44 (0)1778 380 912
E: marketing@degafter.com W: www.degafter.com